



* Optional collars are available for the CPY-5 Canopy Assimilation Chamber from PP Systems.



CPY-5 Canopy Assimilation Chamber

The CPY-5 Canopy Assimilation Chamber is ideal for measurement of net canopy CO₂ flux on low-lying vegetation and fruit. Constructed of rugged polycarbonate, the interior of the transparent chamber includes a user-adjustable PAR (Photosynthetically Active Radiation) sensor and an air temperature sensor near the soil surface. An air mixing fan and custom manifold system ensures uniform circulation within the chamber. An aluminum ring provides a good seal on the soil surface or on collars.* The Water Vapor Equilibrator comes standard.

P	Dime	nsions 145 m 167 ci	ım (H) x 146 mm (Dia) m ²	Cable Length Weight	1.5 m 1.05 kg	
	PAR So Ra Ac Pro	ensor Fully of inge 0 - 300 ccuracy ± 5 μr ecision 1 μmo	cosine corrected 00 μ mol m ⁻² s ⁻¹ nol m ⁻² s ⁻¹ ol m ⁻² s ⁻¹	Temperature So Range Accuracy	ensor (Precision ⁻ -5 °C to 50 °C ± 0.5 °C at 25°C	ſhermistor)
~		The CPY-5 Canopy Assimilation Chamber is compatible with the CIRAS-3 and TARGAS-1 Portable Photosynthesis Systems, and the EGM-5 Portable CO ₂ Gas Analyzer.				
For further informatio	n, please contact us at:		(CIRAS-3	TARGAS-1	EGM-5
SUSTEMS FAX	D Haverhill Road, Suite 301 nesbury, MA 01913 U.S.A. +1 978-834-0505 +1 978-834-0545	•	PP Systems is a registered tradem PP Systems is continuously updat reserves the right to amend prod without notice.	ark of PP Systems, Inc. ing its products and uct specifications	♥ @pţ in con f pps	p_systems 1pany/pp-systems ystems.intl

• All brand names are trademarks of their respective owners.

EMAIL sales@ppsystems.com

Portable • Accurate • Reliable

05.19

ppsystemsinc